



**All Stainless Steel Pressure Gauge #SUS**

Size: 1.5"~10"  
 Pressure connection: SS316; 1/8", 1/4", 3/8", 1/2"; BSPT, NPT, PF  
 Pressure range: 0~1000bar, -1~0bar, -1...0~20bar  
 Accuracy:  $\pm 1.0\%$ F.S.~ $\pm 2.0\%$ F.S.



**Can Vacuum Tester #CVT**

Size: 2.5"  
 Pressure connection: Copper alloy; 1/4"PF  
 Pressure range: -76cmHg~0cmHg  
 Accuracy:  $\pm 2.0\%$ F.S.



**Industrial Glass Thermometer (for autoclave type) #FDT**

Size: 9"  
 Pressure connection: Stainless steel; 3/4"PT  
 Temperature range: 80°C~135°C  
 Accuracy:  $\pm 0.5^\circ\text{C}$



**Bimetal Thermometer (Back Mount Type) #BTT**

Size: 1"~6"  
 Process connection: SS304; 1/4", 3/8", 1/2", 3/4", 1"; BSPT, NPT, PF  
 Temperature range: -50°C~600°C  
 Accuracy:  $\pm 1^\circ\text{C}$



**Sanitary Bimetal Thermometer (Back mount type) #BTT-S**

Size: 2"~6"  
 Process connection: SS304, SS316  
 Blind board dimensions: 0.75"~3"  
 Temperature range: -50°C~600°C  
 Accuracy:  $\pm 1^\circ\text{C} < -20^\circ\text{C} \sim 80^\circ\text{C} >$



**High Precision Pressure Recorder #AT802**

Size: 4"  
 Pressure connection: SS316L; M20\*1.5  
 Pressure range: -100...0kPa~250MPa  
 Power supply: 3.6V lithium battery, AA batteries x3  
 Accuracy:  $\pm 0.02\%$ F.S.~ $\pm 0.2\%$ F.S.



**Flush Diaphragm Sanitary Pressure Transmitter #FDPT-858**

Process connection: SS304, SS316  
 Pressure range: 10kPa~3MPa  
 Output Signal: 4~20mA, 4~20mA+HART  
 Power supply: 10.5~55VDC, 16.5~55VDC (With HART)



**Clamped Flush Diaphragm Pressure Transmitter #FDPT-500 Series**

Pressure connection: SS316L : 2", 2.5"Clamp  
 Electrical connector: Hirschmann connector, 2088 housing  
 Pressure range: -100...0~10kPa...10MPa  
 Accuracy:  $\pm 0.5\%$ F.S.



**Diaphragm Seal Sanitary Pressure Gauge (For Food and Beverage Industry) #DS600**

Thread specifications: G1/2", G1/4", 1/2"NPT, 1/4"NPT  
 Pressure range: 0...1bar~40bar  
 Liquid-filling: Glycerin oil, Silicone oil, Vegetable oil