

Main Specifications **Other Specifications** ▼ Size ▼Housing material 1.38" (35mm) SS430 ▼Installation type ▼ Pointer Back connection Aluminum with red enamel / Aluminum with black enamel ▼Connection Standard: hex nut ▼Dial face Black scale on white board Option: Thread connection 1/16" PF °C / °F single / dual scale Other specification available Common beverage upon request temperature icon ▼ Window Customizable dial face PC Measuring elements ▼ Stem **Bi-metal** Material: SS 304 Temperature sensing area: Outer diameter: 3.8mm last 2" -4" of stem (standard) ▼Temperature accuracy Length: 123mm (standard) 1.5% Other stem outer diameter and ▼Operating temperature Stabilization: 3/4* full scale length available upon request ▼Temperature range Short-time: 1* full scale Min.: -30°C Max.: 200°C (Custom temperature scale range available within -30 to 200°C) ▼Applicable fluid Media that compatible with SS 304 Protection level IP 54

Dimension

Bi-metal Thermometer (For Instant Drink Type) Model: BTT-D Introduction

BTT-D thermometer is suitable for direct liquid temperature measurement such as brewing coffee, heating milk and instant drink.





Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Stem material adopts food grade SS304 Housing material adopts SS430
- Customizable stem outer diameter and length
- Additional protection:
 - silicone rubber protective case (option)
- Optional accessory: fix clamp and plastic stem case (option)



How to order

BTT-D	Bi-metal Thermometer (For Instant Drink Type)						
	Code	Size					
	A 1.38"						
	0	Others (please specify)					
		Code Temperature range					
	Custom	-30 t	o 200°C(200°C (Custom temperature scale range available within -30 to 200°C)			
			Code				
			Н				
			Т				
			0	Other (please specify)			
				Code	3.8 3.8mm		
				0			Other (please specify)
					Code		Stem length
					123		123mm
					0		Other (please specify)
						Code	Other request
						/A	Third party notarized document
						/B	Inspection report (issued by Re-Atlantis)
						/C	Silicone rubber protective case
						/D	Fix clamp
						/E	Plastic stem protective case
						/F	Stem material SS316
						/G	Housing material SS316
						/H	Customized dial face
							(scale, color, beverage icon, etc.)
						/I	Concave panel (for easier reading)
						/J	Round shape stem end (No sharp end)
BTT-D	A	A 0 to 120°C H 3.8 123 Order example: BTT-D-A-(0 to 120°C)-H-3.8-123+/D					