Main Specifications Other Specifications **▼**Thermometer type **▼**Size Single input: 155*56*40mm (L*W*H) 83 / 83D (with data logger) **▼**Screen display Dual input: 5-digit LCD screen dual display 84 / 84D (with data logger) with backlight Max. reading: 9999.9 **▼**Thermocouple type K/J/T/E/R/S/N type **▼**Temperature unit **▼**Temperature range °C / °F / K **▼**Min. measurable K type: -200~1372°C / -328~2501°F temperature value K/J/T/E/N type: 0.1°C J type: -210~1200°C / -346~2192°F R / S type: 1°C **▼**Accuracy T type: -250~400°C / -418~752°F K/J/E/T/N type: $\pm (0.05\% rdg + 0.7^{\circ}C/1.4^{\circ}F)$ E type: -200~1000°C / -346~1832°F (-250~100°C / -418~148°F) R / S type: $\pm (0.05\% rdg + 0.6°C/1°F)$ 0~1767°C /32~3212°F (-100~1372°C / -148~2501°F) N type: R / S type: -150~1300°C / -238~2372°F ±(0.05%rdg+2°C/4°F) (0~1767°C / 32~3212°F)

How to order

DHT-SD		Single / Dual Input Digital Handheld Thermometer					
			de	Thermometer type			
			3	83 type			
			3D	83D type (with data logger)			
			4	84 type			
		84	1D	8	4D type (witl	(with data logger)	
				Code	Oth	er requests	
				/A	Third party documents	notarized	
				/B	Inspection report		
				/C	Tag		
DHT-SD		83D		Order example: DHT-SD-83D			

▼Weight Appx. 200g

Single / Dual Input Digital Handheld Thermometer Model: DHT-SD series Introduction

DHT-SD series single / dual input digital handheld thermometer has a variety of thermocouples to choose from and features wide temperature measurement ranges. For 83D and 84D, the data logging function reads up to 14,000 records. It is suitable for various industrial environments.





Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- Seven thermocouple type available: K/J/T/E/R/S/N
- 5-digit LCD screen dual display with backlight (Max. reading display: 9999.9)
- Max. / Min. / AVG / Time and data storage function
- Over-temperature alarm function
- Enabling and disabling auto power-off function
- Can store 300 reading records manually (For 83/84 type)
- Switchable display T1, T2, or T1-T2 (For 84 / 84D type)
- Data logging memory reading up to 14,000 records (For 83D / 84D type)
- USB / PC serial interface: Windows XP, 7~10 (For 83D / 84D type)