

Main Specifications	Other Specifications
<p>▼ Size 3" (Φ70mm x 35.5mm)</p> <p>▼ Installation type Bottom mount</p> <p>▼ Pressure connection Material: stainless steel 1/4" NPT Other thread spec. is available made-to-order</p> <p>▼ Pressure range Gauge pressure ▼ 0...200kPa to 35MPa Negative pressure ▼ -30 to 0inHg</p> <p>▼ Applicable fluid Liquid and gas that compatible with stainless steel</p> <p>▼ Ambient temperature 0-50°C</p> <p>▼ Ambient humidity <95%RH</p> <p>▼ Atmospheric pressure 86-106kPa</p>	<p>▼ Case Reinforced plastic ABS</p> <p>▼ Screen display 4.5-digit LCD display Display range ▼ -19999~9999</p> <p>▼ Screen size 46 (W) x 23 (H)mm</p> <p>▼ Refresh rate 10 times/sec</p> <p>▼ Power supply AAA battery x2</p> <p>▼ Pressure unit psi, inHg, oz/in², MPa, inWC, ftWC, kg/cm², kPa, bar</p> <p>▼ Accuracy ±1.0% F.S. (standard) ±0.5% F.S. (options)</p> <p>▼ Weight 190g</p> <p>▼ Other requests (Option) Third party notarized documents Inspection report Tag</p>

Economical Digital Pressure Gauge Model: DPG-0.5B2.5 (4.5CD) Introduction

DPG-0.5B2.5 (4.5CD) economical digital pressure gauge is lightweight, low power consumption, and complete basic functions, which is suitable for general pressure measurement needs.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Accuracy 0.5%F.S.
- Switchable pressure units
- Switchable max./min. pressure value display
- With current remaining battery indicator

How to order

DPG-0.5B2.5 (4.5CD) Economical Digital Pressure Gauge									
Std.	Spec.	Code	Item	Code	Item	Code	Item	Code	Item
2N	Pressure connection	2N	1/4" NPT	0	Others	-	-	-	-
Custom	Pressure range	Gauge pressure : 0...200kPa to 35MPa Negative pressure : -30 to 0inHg							
10	Accuracy	10	±1.0%F.S.	05	±0.5%F.S.	-	-	-	-
/B	Other requests	/A	Third party notarized document						
		/B	Inspection report (issued by Re-Atlantis)						
		/C	Tag						

Order example: DPG-0.5B2.5(4.5CD) - 2N - (0-30MPa) - 10 - /B