ATLANTIS

Main Specifications

▼Size 4″

- ▼ Pressure connection Thread spec.: G1/4" Thread type: Female thread Material: Stainless steel
- Other thread material and spec. is available made-toorder
- ▼ Pressure range
- For details please refer to pressure range table
- ▼Applicable media
- With anti-corrosive adapter
- can resist strong acid and alkali Ambient temperature
- -20~80°C
- ▼Operating temperature -10~60°C
- ▼Accessory (Option)
- Anti-corrosive adapter

▼ Case Aluminum alloy Screen display 5-digit display with backlight ▼Pressure unit Standard: MPa, kg/cm², kPa, psi Option: bar, mH₂O, mmHg ▼ Power supply 3A battery*3 / rechargeable battery Accuracy ±0.05% F.S. ▼Overpressure 1.5*F.S. ▼Other requests (Option) Third party notarized documents Inspection report Tag

Other Specifications

High Precision Digital Pressure Gauge Model: DPG-GH0.05 Introduction

DPG-GH0.05 digital pressure gauge features wide pressure range and highest accuracy can up to 0.05%. With anti-corrosive adapter can resist strong acid and alkali.



Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- 5-digit screen display with backlight
- Switchable pressure unit up to 7
- Highest accuracy up to 0.05%
- Peak-hold function

Pressure range

Code	Pressure range
P1	-100~0 kPa
P2	0~160 kPa
P3	0~250 kPa
P4	0~400 kPa
P5	0~600 kPa
P6	0~1 MPa
P7	0~1.6 MPa
P8	0~100 MPa
0	Other pressure range is
0	Other pressure range is available made-to-order.

How to order

Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem
04	Size	04	4″	-	_	-	_	-	-
2G	Thread spec.	2G	G1/4″	0	Others	-	_	-	_
SS	Thread material	SS	Stainless steel	0	Others	-	-	-	_
P2	Pressure range	Please re	fer to Pressure/Com	ipound Pi	ressure Range and	Accuracy	Table and select cor	rrespondin	ng code
P2		Please re	fer to Pressure/Com	pound Pi	ressure Range and	Accuracy	Table and select cor	rrespondin	ng code
P2 3A		Please re 3A	fer to Pressure/Com 3A battery*3	pound Pi	ressure Range and Rechargeable battery	Accuracy	Table and select cor	rrespondin	ng code
	range Power				Rechargeable	Accuracy	Table and select cor	rrespondir	ng code
	range Power				Rechargeable	Accuracy	Table and select cor	rrespondir	ng code
3A	range Power supply	3A 05	3A battery*3 ±0.05%	R —	Rechargeable battery —	Accuracy			ng code
3A 05	range Power supply	3A 05 /A	3A battery*3 ±0.05% Third party notaria	R — zed docu	Rechargeable battery — ment	Accuracy			ng code
3A	range Power supply Accuracy	3A 05	3A battery*3 ±0.05%	R — zed docu	Rechargeable battery — ment	Accuracy			ng code

Order example: <u>DPG-GH0.05</u> - <u>04</u> - <u>2G-</u> <u>SS</u> - <u>P2</u> - <u>3A</u> - <u>05</u> - <u>/B</u>