Main Specifications

▼ Size

4″ (105mm) ▼Pressure connection

Thread spec.: M20*1.5, G1/4", G1/2"、 1/2"NPT、1/4"NPT Other thread size and type are available made-to-order Material: SS304 ▼Pressure range

Please refer to pressure range table

▼Applicable media Liquid and gas that compatible with Stainless steel

Operating temperature

-5~40°C

Other Specifications

▼Case material SS304

▼ Screen display 5-digit LCD display with white

backlight Main and sub-line display

▼Pressure unit

MPa, kPa, bar, Pa, mbar, psi, mmHg, mH₂O, Torr, kgf/cm² ▼Power supply

▼ Power supp

AA battery x3 USB power supply

▼Accuracy

±0.05%F.S. / ±0.1%F.S.

▼ Stability

±0.1%F.S. / year

▼Sampling rate 1-10 times / sec.

(This can be set by user)

▼Overpressure

150% (>10MPa) 200% (≤ 10MPa)

- ▼Temperature compensation 0~40°C
- ▼Accessory
- Portable case
- USB power line



High Accuracy Digital Pressure Gauge Model: DPG-X002 Introduction

DPG-X002 adopts high accuracy ADC and highspeed microprocessor as measuring elements. It features wide pressure range, lower power consumption, peak and valley value display, and temperature display. Suitable for mechanical and electronic industry, pressure laboratory, and automated construction machinery.





Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM service
- Lower power consumption, up to 3600 working hours with AA batteries.
- 5-digit screen display with white backlight, with peak and valley value & temperature display function
- Wide pressure range for selections
- 10 switchable units: MPa, kPa, bar, Pa, mbar, psi, mmHg, mH₂O, Torr, kgf/cm²
- Accuracy can up to 0.05%F.S.

Pressure Range Table

Code	Pressure range
P1	1…2.5…25 kPa
P2	40…60…250 kPa
P3	0.4…0.6…4 MPa
P4	6…10…25 MPa
P5	40…60…160 MPa
P6	-2.5~2.5…5…(-100~1000) kPa
P7	0~10…25…1000 kPa
P8	0~10…25…40…60…100…250…400…600 kPa
P9	0~1…1.6 MPa

How to Order

DPG-X00)2 High Ac	curacy [Digital Pressure C	Gauge						
Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem	
4N	Thread	М	M20*1.5	G2	G1/4″	G4	G1/2″	4N	1/2"NPT	
	spec.	2N	1/4"NPT			0	Others	—	_	
Custom	Pressure type	Please refer to Pressure Table and select corresponding code								
А	Accuracy	Α	±0.1% F.S.	В	±0.05%F.S.	_	-	—	_	
/B	Other requests	/A	Third party notarized document							
		/B	Inspection report (issued by Re-Atlantis)							
		/C	Tag							

Order example: <u>DPG-X002</u> - <u>4N</u> - <u>P4</u> - <u>A</u> - <u>/B</u>