Main Specifications Other Specifications ▼Size **▼**Top cover 9" Screw Fixed **▼**Window **▼**Housing Aluminum alloy with black **▼**Stem enamel Material: Stainless steel **▼**Liquid in glass Length without Mercury thread:65mm*Φ12mm **▼**Dial <Standard> White board with black scale <Options: Length without V-shape thread 50mm or others> ▼ Measuring elements **▼**Process connection Thermal expansion linearity 3/4" PT of mercury ▼Temperature range **▼**Accuracy Min.: 80°C Max: 135°C **▼**Operating temperature **▼**Temperature error Steady: 3/4* full scale Standard: calibrated temp. Short time: 1* full scale Every ±4°C **▼**Other requests (Option) max. error: ±0.25% F.S Delivery inspection report **▼**Application Food / Pharmaceutical / Third party notarized Canning industry documents Thermometer casing

Industrial Glass Thermometer (for autoclave type)

Model: FDT

Introduction

FDT thermometer are specially designed for high temperature sterilization equipment in food, pharmaceutical, and canning industry. The thermometer may have an optimum application with remote recording thermometer and pressure gauge.





Due to the variety of customization, the picture is only for reference, please confirm the actual item with our sales. (If there is any change on specification, please take the latest version as standard.)

Features

- OEM Service
- Mercury thermometer with well characteristic of constant thermal expansion.
- Red scale reflector to ensure legibility

How to order

- · ·										
FDT Industrial Glass Thermometer (for autoclave type)										
Std.	Spec.	Code	ltem	Code	ltem	Code	ltem	Code	ltem	
9	Size	9	9″	_	_	_	_	_	_	
6P	Process connection	6P	3/4" PT	_	-	-	-	_	-	
65	Stem Length	65	65mm	50	50mm	0	Others	_	-	
Custom	Temperatur e range	80 C~135 C								
/B		/A Third party notarized document								
	Other	/B	Inspection report (issued by Re-Atlantis)							
	requests	/C	Tag							
		/D	Thermowell							

Order example: FDT - 9- 6P - 65 - (80°C~120°C)- /B